



# SUPPLEMENTARY MANUAL

for QSE-1 + QSH-P4A

REMOVE THE FRAME  
COVERS BELOW MAIN SEAT.



REMOVE THE MAIN SEAT.



REMOVE THE  
STEERING DAMPER HOLDER.



# Kawasaki ZX-10R

2006-2007



REMOVE THE FUEL TANK.



REMOVE THE AIRBOX.



PLUG QSH CONNECTORS IN-LINE  
WITH THE IGNITION COIL  
CONNECTORS.  
(BLACK, 2-POLE CONNECTORS BELOW AIRBOX)



# Kawasaki ZX-10R

2006-2007



**CONNECT QSH BLACK WIRE  
TERMINAL TO CHASSIS GROUND.**



### **MOUNT THE QSE SENSOR.**

(USE THE NEW BOLT AND WASHERS SUPPLIED WITH  
THE UNIT. MAKE SURE TO PLACE ONE WASHER ABOVE  
THE SENSOR AND ONE WASHER BELOW THE SENSOR.  
TIGHTEN THE SCREW BY 3-4 NM.

WHEN TIGHTENED, DO NOT TRY TO ROTATE THE  
SENSOR BODY.)



**TYPICAL POSITION FOR THE  
QUICKSHIFTER EASY.**

