

Honda NT650V Deauville

1998-2005



SUPPLEMENTARY MANUAL

for GPX-WSS

**REMOVE THE SEAT.
REMOVE BLACK FRAME COVERS
BELOW FUEL TANK.
LIFT UP OR REMOVE THE
FUEL TANK.**



**MOUNT GPX-WSS SENSOR
TO FRONT OR REAR WHEEL.**

(WHEEL SPEED SENSOR WILL READ
THE BOLT HEADS OF THE REAR BRAKE DISC OR
THE BOLT HEADS OF THE REAR WHEEL SPROCKET.
IF REAR WHEEL MOUNT IS NOT POSSIBLE,
YOU CAN ALSO INSTALL THE SENSOR
AT THE FRONT WHEEL.)



**CONNECT GPX RED WIRE TO
A SWITCHED +12V LEAD AND
CONNECT GPX BLACK WIRE TO
GROUND LEAD.**

(EXAMPLE: PARKING LIGHT
TRANSPARENT, 2-POLE CONNECTOR WITH
BROWN (SWITCHED +12V) AND GREEN (GND) WIRES)



Honda NT650V Deauville

1998-2005



**CONNECT GPX BLACK/GREEN WIRE
TO
YELLOW/BLUE WIRE OF
IGNITION TRANSFORMER
FOR REAR CYLINDER.**
(UNDER BETWEEN FUEL TANK AND SEAT,
NEAR TO REAR CYLINDER)

